

Maintenance for Poured Rubber Surfaces

In order to maintain the wear course of your EPDM / TPV surface, we recommend routine inspection and cleaning. Follow the guidelines outlined in your maintenance manual. In addition, in order to preserve the life of your surface, a roll coat/spray coat application is recommended every 18-24 months. Our specially formulated urethane binder is applied and penetrates the wear course to restrengthen the bonding of the granules. The coating also provides UV protection from sun damage and helps minimize cracks and granulation.

It is also important to repair small holes and cracks as soon as they become apparent. Our PIP repair kit below can help with that. When a surface is beyond patching, overlays and/or re-tops are cost effective solutions versus complete removal and replacement of your entire surface. Contact us if your surface is displaying any of the following common issues. We can help with long-term maintenance and short term repairs as well.



SPIDER CRACK



WEAR HOLE



THINNING



COLOR SEAM SEPARATION



PERIMETER SEPARATION



Fibar All-In-One PIP Repair Kit

Our DIY Kit for patch repairs comes in a wide variety of color mix options - 100% color or 50/50 color/black mix. Patch wear course holes with standard circle patches or create fun shapes to add play value to your surface. The all-in-one kit is shipped in a bucket and includes:

- Approximately 5 square feet of pre-selected color rubber granules
- 1 utility knife
- 1 small brush
- 1 container of urethane binder
- 1 pair of gloves
- 1 trowel

